

## Product Information

Transparent Application Tape based on a dimensionally stable polypropylene film embossed on one side.

Suitable for transferring self adhesive signs, logos and lettering with matt or brilliant surface.

Especially to be emphasised are the following properties:

- The plasticiser resistant adhesive guarantees a strong initial tack to all types of vinyl films. The Application Tape is easily removed without leaving any residue, even after being left for a period of time.
- The acrylic adhesive is resistant against humidity and therefore ideal for wet application.
- The high transparency of the film favours application of small letters and logos.
- The embossed surface allows the film to be easily unrolled without accumulation of static electricity.

## Technical Data

<b>Carrier:</b>	Polypropylene film, Orange peel surface	
<b>Adhesive:</b>	Acrylic	
<b>Adhesion [N/cm]:</b>	1,20	+/- 10 %
<b>Thickness [mm]:</b>	0,09	+/- 5 %

## Standard Dimensions

1.220 mm x 100 m  
1.000 mm x 100 m

## Safety Data Sheet

When used under normal conditions, this product does not generate or release any dangerous substances or hazardous chemicals. This is a non-hazardous product in accordance with the current GefStoffV and EU criteria. Therefore it is not necessary to prepare a Material Safety Data Sheet for this product. The Safety Data Sheet serves only to comply with the regulation to supply information in accordance with REACH Regulation (EC) No. 1907/2006 and is available on request. This product is not a hazardous product with regards to transportation legislation; neither does it contain substances that are hazardous to water within the meaning of the federal water act. After use, dispose of the waste product in accordance with the local / national authorities.