

Substrate		DIN 60001	100 % polyester
Weave		DIN ISO 9354	woven fabric
Weight approx.		DIN EN ISO 2286-2	335 g/m ² (without liner) 430 g/m ² (with liner)
Fire retardancy		DIN 4102 B1	yes
Application			indoor
Width		DIN EN ISO 2286-1	max. 152 cm / 60 inch (see overview)
Print side			outside
Roll length			30 ± 0,5 m
Care instruction		DIN EN 12956	scrub resistant (grade 5) according to instruction*
Type of ink			all kinds of solven inks, UV-curable inks, latex inks

Advantages

- fast crease recovery
- reverse film easy to remove
- repositionable
- trimming cold (no fraying)
- easy handling, print & cut
- able to plott

Applications

- wall covering**

* please have a look at the cleaning instructions on www.jm-mediatex.com

** please test in advance; the adhesive behavior depends on the surface applied;
please have a look at the processing instructions on www.jm-mediatex.com



All details are nominal values and are subject to change within usual tolerances (± 5 %). The information provided in this document is based on current knowledge and experience. They do not exempt a manufacturer/processor from carrying out their own tests and trials as their in-house handling and manufacturing processes can have a significant range of influences on outcomes. Application, utilisation and processing of products is taking place outside of our control and are therefore the sole responsibility of the manufacturer/processor. date: 01/2020