

# Scotchgard™ Paint Protection Film Pro Series 4.0

## Technical Data Sheet

### Description

Scotchgard™ Paint Protection Film Pro Series 4.0 protects automotive paint and other vulnerable surfaces from stone chips, scratches, bug damage, road tar stains, automotive fluid stains, and punishing outdoor weathering.



Film Layer

Adhesive Layer

Release Liner

### Physical Properties

Film type	PU film with Top-Coat
Color	Transparent
Surface appearance	Glossy
Nominal thickness	203 µm (incl. adhesive)
Adhesive type	Pressure sensitive Acrylic adhesive (suitable for wet application)
Liner type	PET
Typical substrates	Automotive paint
Tensile Strength	> 1600 N/cm <sup>2</sup>
Elongation	> 250 %

### Product Information

Staining resistance	★ ★ ★
Stone chip protection	★ ★
Scratch resistance	★ ★ ★
Abrasion resistance	★ ★
Conformability	★ ★ ★

(maximum 3 stars)

### Shelf life

12 months in original packaging. Store in dry, dark conditions at +15°C to +25°C and a maximum of 50% relative humidity. Avoid direct sunlight.



## **Additional user information**

The product is equipped with an additional surface protection film that needs to be removed before processing.

## **Limitation of End Use**

3M specifically does not recommend or warrant any use other than described in local instructions, but please contact us to discuss your needs to recommend other products.

## **Additional Information**

To request additional product information see address below.

## **IMPORTANT NOTICE:**

All statements, technical information and recommendations contained in this document are based upon tests or experience that 3M believes are reliable. However, many factors beyond 3M's control can affect the use and performance of a 3M product in a particular application, including the conditions under which the product is used and the time and environmental conditions in which the product is expected to perform. Since these factors are uniquely within the user's knowledge and control, it is essential that the user evaluates the 3M product to determine whether it is fit for a particular purpose and suitable for the user's method or application.

Values presented have been determined by standard test methods and are average values not meant to be used for specification purposes.

All questions of warranty and liability relating to this 3M product are governed by the terms of the respective sale subject, where applicable, to the prevailing law.

3M is a trademark of 3M Company.

3M Deutschland GmbH  
Automotive & Aerospace  
Solution Division  
Carl-Schurz-Str.1  
41453 Neuss

3M Schweiz GmbH  
Automotive & Aerospace  
Solution Division  
Eggstrasse 93  
8803 Rüslikon

3M Österreich GmbH  
Automotive & Aerospace  
Solution Division  
Kranichberggasse 4  
1120 Wien

Supersedes: