



www.xlam.biz

Xlam

XL1600 cold 2.0



main rolls Ø

130 mm

max. temperature

60 °C

max. material thickness

30 mm

Functional design ✓



Pneumatic lifting ↑



Optional Blades Kit for trimming 🍷



>XL1600 cold 2.0

PNEUMATIC COLD LAMINATOR



www.xlam.biz / info@xlam.biz

Unique features!

Cold roll-to-roll pneumatic laminator 1600 mm.
Take-Up system included. **Silicone roll (heated) 130mm**,
maximum temperature 60°C. **Material thickness
up to 30mm.**

Quick and easy to use, it allows you to save labor and
improve productivity by increasing the quality of your work.
Moreover, from today you can also laminate without liner
with "**linerless**" laminations.

High efficiency

No crease or bubble, it guarantees excellent results even
at temperatures below 60°C. **Equipped with footswitch
feeding**, it allows the operator to keep both hands free for
the rolling of wider supports.

Safety warranty

The **photocell sensor** prevents you place your hands near
roll during the lamination. The emergency shutdown button
is clearly visible on the front of the machine.

Product code
XL1600C2.0

Main silicon rolls diameter
130 mm

Packaging
anti-shock wooden

Maximum laminating film width
1600 mm

Main roll moving
by air compressor

Dimensions (l x h x p)
1980 x 1350 x 630 mm

Maximum material thickness
30 mm

Footswitch feeding
included

Packaging dimensions (l x h x p)
2250 X 720 x 810 mm

Maximum temperature
60 °C

Take-Up system
included

Machine / packaging weight
115 kg / 135 kg

Minimum-maximum speed
2,30 - 11,55 lmt/min

Heating method
internal with resistance

Safety
photocell / CE certification

Temperature-speed control
Micro Control

Maximum power / Voltage
2500 W / 220 v - 50 hz

Warranty
12 months



Authorized Reseller