

KernowJet FloorShark Floor Graphics Film 170TFG

170TFG is a textured white print receptive PET film, with an optimised pressure sensitive adhesive for floor graphic applications

Property	Typical Value	Unit	Test Method
Construction			
Total Thickness	315 +/- 6	μ	Electronic micrometer
Total Weight	385 +/- 8	gsm	Internal method
Face Material (without PSA)			
Thickness	170 +/- 4	μ	Electronic micrometer
Weight	224 +/- 5	gsm	Internal method
Adhesive			
Thickness	35 +/- 5	μ	Electronic micrometer
180° Peel Adhesion (SS)	11 +/- 1	N/25mm	FINAT 1 (Modified) 200μ Thickness / 25mm strip/ 30min dwell
Adhesive Application Temperature	+5 to +50	°C	Internal Method
Adhesive Service Temperature	-40 to +180	°C	Internal Method
Liner			
Liner Thickness	115 +/- 3	μ	Electronic micrometer
Liner Weight	130 +/- 3	gsm	Internal method

Attributes

- Unique sharkskin coating, ink absorbent & drying tough
- No lamination required
- R10 slip certified
- Durable surface, resists pallet truck scuffing & stiletto heels
- Also perfect for application to short-pile carpet tiles
- Easy to apply & easy to remove

Recommended Conditions

Print room	10°C - 30°C	30% - 65% RH
Usage	-40°C – 180°C	10% - 90% RH
Storage	10°C - 20°C	20% - 50% RH

Shelf Life: 18months (Original packaging and under recommended storage conditions).

Printability

(Eco) Solvent	✓✓✓
Latex	✓✓✓
UV	✓✓✓

Kernow Coatings Ltd
Kernick Road
Penryn, Cornwall
TR10 9DQ

www.kernowcoatings.com
sales@kernowcoatings.com
T: +44 (0)1326373147
F: +44(0)1326376614

Registered in England
No. 1092182
A Member of the Sensitiser
Group of Companies

The information provided herein is correct to the best of our knowledge. No liability for any errors, facts or opinions is accepted..

We recommend users make their own assessments to satisfy themselves as to the suitability of this product for their application.

Version 19/02

Copyright Sensitisers Group 2019